

Jøtul F 100 Nordic QT


Non-Catalytic Woodstove

Jøtul has done it again! Based on the overwhelming success of its gas stove cousin and previously introduced in Europe in 2001 with remarkable acceptance, the Jøtul F 100 Nordic QT, continues our tradition of clean-burn woodburning design and innovation. With its decorative latticework based on a Norwegian sweater pattern, this stove is the perfect space heater for cottages, camps & smaller living areas.

Classic Matte Black
Paint



Blue/Black
Porcelain Enamel



Jøtul F 100 Nordic QT shown here with Blue/Black Porcelain Enamel.

Features

- Manufactured with built-in double wall rear & bottom heatshields, which provide excellent clearances
- Durable cast iron firebox
- Alcove approved for US and Canada
- Incorporates non-catalytic clean burn technology
- Ability to rear or top vent
- Air washed glass provides a clear view of flames

- Proven spring-loaded door latch system recognized as industry's finest
- 5 year limited warranty

Options

- Flue collar heatshield (used with double wall connector pipe)
- Matte Black Paint or Blue/Black Porcelain Enamel



| | | |
|--|------------------------------|------------|
| Model | Jøtul F 100 Nordic QT | |
| Combustion Technology | Non-Catalytic Clean Burn | |
| Construction | Cast Iron | |
| Height | 22 1/2" | |
| Width | 21" | |
| Depth** | 17 1/2" | |
| Weight | 215 lbs. | |
| Flue Size | 6" | |
| Height to Top of Flue | | |
| Top | 24" | |
| Rear | 21 3/4" | |
| Log Length | 16" | |
| Maximum Heat Output¹ | 35,000 BTU/hr (3.0 kg wood) | |
| Heating Capacity² | 600-1,000 sq ft | |
| Overall Efficiency³ | 71% | |
| Emissions | 3.0 grams/hr | |
| Burn Time | 3-6 hours | |
| Clearance-Top Vent | US | CAN |
| Rear | 11" | 280 mm |
| Side | 15" | 380 mm |
| Corner | 10" | 255 mm |
| Clearances with Jøtul Flue Collar Heatshield and Type E Double Wall Insulated Chimney Connector | | |
| Rear | 8" | 205 mm * |
| Side | 17" | 430 mm * |
| Corner | 10" | 255 mm * |

¹ Maximum Heat Output based on kg of dry wood burned per hour.

² Heating Capacity and Maximum Burn Time will vary depending on design of home, climate, wood type and operation.

³ Overall Efficiency is based on a burn rate of .75 kg wood per hour.

* Based on top exit only.

** Depth is overall depth with ashlip and smoke outlet included.

All Jøtul woodstoves meet US EPA emission limits for wood heaters sold after July 1990, and are tested and listed to ANSI/UL 1482 and CAN/ULC S627.90. They are intended for installation in accordance with NFPA 211 or CAN/CSA B365.

Always refer to your Jøtul Installation and Operation Instructions for specific information regarding the installation requirements for your stove. Contact local building or fire officials regarding restrictions and installation inspection requirements in your area.

Some settings for the photographs are for aesthetic purposes only and may not comply with installation requirements. Materials, specifications, accessories, colors, and models are subject to change without notice. Some models are shown with optional accessories. BTU ratings are to be used as a guideline only, and do not imply a guarantee of the heating capacity of the unit.

Our 5 year warranty: a cast iron promise of quality. Jøtul guarantees the quality of its cast iron components against any defects in materials or workmanship for five years, subject to the exclusions and limitations noted on our warranty. For complete details, ask your Authorized Jøtul Dealer.

Jøtul North America
400 Riverside Street
P.O. Box 1157
Portland, Maine 04104

www.jotulflame.com

Authorized Jøtul Dealer

February 2002

Ask your Authorized Jøtul Dealer about our full line of cast iron wood and gas stoves, inserts and fireplaces.

Jøtul F 100 Nordic QT

